## **Mineral Fiber Rubber Sheet**



#### Code: KXITEB701 Description

Mineral Fiber Rubber Sheet is made from Mineral Fiber fiber, rubber and heat-resisting materials, compressing it into thick paper.



#### Mineral Fiber Rubber Sheet Item no.: KXITEB701

- \* Economical sheet
- \* Wide range of pressure and temperature

### **Typical Application**

- \* Used for equipment in water, steam, etc.
- \* Used as sealing material in the joint of pipeline

#### **Technical Data**

Mineral Fiber Rubber Sheet Physical Property											
GB/T539-1995											
Item	B70145	B70140	B70135	B70130	B70120	B70115					
Color											
Tensile											
Strength≥	19.0	15.0	12.0	9.0	6.0	5.0					
Мра											
Aging	0.9										
Coefficient≥	0.8										
Burning loss	2	8	30		30						
≤ %											
Density g/cm3	1.6~2.0										
Compressibi	12+/-5										
lity %	1277-5										
Rebound	4	5	40		35						
Degree											
Pliability	No crack										
Stress	50										
relaxation $\leq$	50										
	With the										
Steam	temperature	temperature	temperature	temperature	temperature	temperature					
Airtightness	of	of	of	of	of	of					
	440~450oC	390~400oC	340~350oC	290~300oC	200~220oC	140~150oC					

Copyright © 2014-2015 Ningbo Kaxite Sealing Materials Co., Ltd. No.134,Huancheng North Road,Jiangbei District, Ningbo City,Zhejiang Province,China (Zip:315020) Website:<u>http://www.seal-china.com</u> E-mail:<u>sales@seal-china.com</u>

# **Mineral Fiber Rubber Sheet**

Code: KXITEB701



	and the								
	pressure of								
	11~12Mpa,	8~9Mpa,	7∼8Mpa,	4~5Mpa,	2~3Mpa,	1.5~2Mpa,			
	keep for 30								
	min without								
	puncture	puncture	puncture	puncture	puncture	puncture			

#### Dimensions

4100x1500x(0.5~6.0)mm, 2000x1500x(0.5~6.0)mm 1500x1360x(0.5~6.0)mm, 3810x1270x(0.5~6.0)mm 1270x1270x(0.5~6.0)mm, 1500x1500x(0.5~6.0)mm The other size is optional or according to the requirements of customers.